WHAT IS CLAIMED IS:

1. A digital information embedding device, comprising:
    input means receiving a digital content input;
    feature value detection means detecting a feature value of at least a partial area of said digital content input; and
    information embedding means modifying said area, based on said feature value detected.

2. The digital information embedding device of claim 1, wherein:
    said input means receives an image; and
    said feature value detection means detects as said feature value a value indicating a level allowing a human visual sense to perceive a pixel value vary.

3. The digital information embedding device of claim 2, wherein said information embedding means changes a value of a pixel in said area only when said feature value detected is a value preventing the human visual sense from perceiving the pixel value vary.

4. The digital information embedding device of claim 2, wherein said information embedding means includes range determination means setting a larger variation range for the pixel value if said feature value detected has a higher level allowing the human visual sense to perceive the pixel value vary, and said information embedding means changes a value of the pixel in said area within said variation range determined.

5. The digital information embedding device of claim 1, wherein:
    said information embedding means includes range determination means determining a variation range for the pixel value, based on said feature value detected; and
    said information embedding means changes a value of the pixel in said area within said variation ranged determined.

- 15 -

6. The digital information embedding device of claim 1, wherein said feature value detection means includes transform means orthogonally transforming a value of a pixel in said area to detect as said feature value at least one high frequency component of a frequency component orthogonally

5   transformed.

7. The digital information embedding device of claim 1, wherein:
said input means receives an image;
said feature value detection means detects as a feature value a value in brightness of a pixel included in said area; and

5   said information embedding means includes range determination means setting a larger variation range for a pixel value if said value in brightness detected is smaller, and said information embedding means changes a value in brightness of the pixel in said area within said variation range determined.

8. A computer-readable recording medium having recorded therein a program provided to embed digital information and causing a computer to perform the steps of:
receiving a digital content input;

5   detecting a feature value of at least a partial area of said digital content input; and
modifying said area, based on said feature value detected.

9. The recording medium of claim 8, wherein:
the step of receiving includes the step of receiving an image; and
the step of detecting includes the step of detecting as said feature value a value indicating a level allowing a human visual sense to perceive a

5   pixel value vary.

10. The recording medium of claim 9, wherein the step of modifying changes a value of a pixel in said area only when said feature value detected is a value preventing the human visual sense from perceiving the pixel

value vary.

11.   The recording medium of claim 9, wherein the step of modifying includes the step of setting a larger variation range for the pixel value if said feature value detected has a higher level allowing the human visual sense to perceive the pixel value vary, and of changing a value of the pixel in said

5   area within said variation range determined.

12.   The recording medium of claim 8, wherein the step of modifying includes the step of determining a variation range for the pixel value, based on said feature value detected, and of changing a value of the pixel in said area within said variation range determined.

13.   The recording medium of claim 8, wherein the step of detecting includes the step of orthogonally transforming a value of a pixel in said area to detect as said feature value at least one high frequency component of a frequency component orthogonally transformed.

14.   The recording medium of claim 8, wherein:
the step of receiving includes the step of receiving an image;
the step of detecting includes the step of detecting as a feature value a value in brightness of a pixel included in said area; and

5   the step of modifying includes the step of setting a larger variation range for a pixel value if said value in brightness detected is smaller, and of changing a value in brightness of the pixel in said area within said variation range determined.

15.   A method of embedding digital information, comprising the steps of:
receiving a digital content input;
detecting a feature value of at least a partial area of said digital

5   content input; and
modifying said area, based on said feature value detected.

16.   The method of claim 15, wherein:

the step of receiving includes the step of receiving an image; and

the step of detecting includes the step of detecting as said feature value a value indicating a level allowing a human visual sense to perceive a pixel value vary.

5

17.   The method of claim 16, wherein the step of modifying changes a value of a pixel in said area only when said feature value detected is a value preventing the human visual sense from perceiving the pixel value vary.

18.   The method of claim 16, wherein the step of modifying includes the step of setting a larger variation range for the pixel value if said feature value detected has a higher level allowing the human visual sense to perceive the pixel value vary, and of changing a value of the pixel in said area within said variation range determined.

5

19.   The method of claim 15, wherein the step of modifying includes the step of determining a variation range for the pixel value, based on said feature value detected, and of changing a value of the pixel in said area within said variation range determined.

20.   The method of claim 15, wherein the step of detecting includes the step of orthogonally transforming a value of a pixel in said area to detect as said feature value at least one high frequency component of a frequency component orthogonally transformed.

21.   The method of claim 15, wherein:

the step of receiving includes the step of receiving an image;

the step of detecting includes the step of detecting as a feature value a value in brightness of a pixel included in said area; and

5

the step of modifying includes the step of setting a larger variation range for a pixel value if said value in brightness detected is smaller, and of

changing a value in brightness of the pixel in said area within said variation range determined.